



- 1 DRAWING DEPICTS 2 3/4\"/>

- NOTES:
1. APPLICABLE TO COMMERCIAL LOCKS (WITH ANSI/ASA STRIKE):
 - GRADE 2; EL, EM
 - LOCKS WITH 64 mm CENTER-TO-CENTER DISTANCE BETWEEN REMOVABLE POSTS
 2. DRAWING DEPICTS METAL FRAME AND HOLLOW METAL DOOR WITH:
 - 2-3/4\"/>
 3. DOOR AND FRAME REQUIRE ADEQUATE REINFORCEMENT TO SUPPORT THE LOCK BODY, THE LATCH AND THE STRIKE. DEPICTED DESIGNS ARE OPTIONAL.
 4. REFERENCE:
 - ANSI A156.115
 - DOOR PREP 161
 5. IT IS RECOMMENDED THAT PHYSICAL HARDWARE BE ORDERED AND VERIFIED BEFORE STARTING THE PRODUCTION OF DOORS.

DIMENSIONS INCHES
MM

DO NOT SCALE DIMENSIONS ON DRAWING

TOLERANCES			CANAROPA			
Ø.XX	Ø.XXX	DEGREES	DRAWN	DATE	TITLE	
± 0.03	± 0.010	± 0.5	CC	19-OCT-17	DOOR & FRAME PREP FOR COMMERCIAL CYLINDRICAL LOCKS FOR 1 3/4\"/>	
MATERIAL			APPR'D	DATE	TITLE	
N/A				19-OCT-17	DOOR & FRAME PREP FOR COMMERCIAL CYLINDRICAL LOCKS FOR 1 3/4\"/>	
FINISH			APPR'D	DATE	SCALE 1:1	DWG NO
N/A			REVISION		REV-	CAN-DP-ANSI-A156.115-64mm