



NOTES

- 1 DRAWING DEPICTS 2 3/4" BACKSET. IF 2 3/8" OR OTHER BACKSET IS DESIRED, CHANGE THE BACKSET TO THE DESIRED ONE
  - 2 DRAWING DEPICTS 1 3/4" DOOR THICKNESS, FOR OTHER DOOR THICKNESS POSITION THE LATCH CENTER AT HALF OF THE DOOR THICKNESS AND ADJUST STRIKE POSITION ACCORDINGLY
  - 3 FOR DRIVE-IN LATCHES DRILL 3 1/32" HOLE AND DO NOT MAKE CUTOUT FOR FACEPLATE
  - 4 CONFIRM LATCH FACEPLATE AND STRIKE PLATE CORNER TYPE (SQUARE OR ROUNDED) AND PREPARE THE REQUIRED CUT-OUTS ACCORDINGLY ON THE DOOR EDGE AND DOOR FRAME.
5. APPLICABLE TO RESIDENTIAL DOOR LOCKS WITH  
- FULL D-STRIKE OR T-STRIKE
6. DRAWING DEPICTS WOOD DOOR AND WOOD FRAME WITH  
- 2-3/4" BACKSET  
- 1-3/4" DOOR THICKNESS

DIMENSIONS INCHES  
MM

DO NOT SCALE DIMENSIONS ON DRAWING

TOLERANCES			CANAROPA			
Ø.XX	Ø.XXX	DEGREES	DRAWN	DATE	TITLE	
± 0.03	± 0.010	± 0.5	CC	13-JAN-17	DOOR & FRAME PREP FOR RESIDENTIAL 100 SERIES LOCKS FOR 1 3/4" THICK WOOD DOORS 2 3/4" BACKSET AND 2-1/8" BORE	
MATERIAL N/A			APPR'D	DATE		
				13-JAN-17		
FINISH N/A			APPR'D REVISION	DATE	SCALE 1:1	DWG NO
					REV-	CAN-DP-100SER-E-218-234