



EM



EL



- Type** • Cylindrical lock
- Certifications**
  - Conforms to ANSI/BHMA A156.2, Series 4000, Grade 2
  - cULus listed, 3hr fire-rating
  - UL 10C Positive Pressure Rating
  - Meets ADA requirements
  - 1 Year limited warranty
- Door Thickness** • 1<sup>3</sup>/<sub>8</sub> – 1<sup>3</sup>/<sub>4</sub>" (35–44.5 mm)
- Handing** • Non handed
- Backset**
  - 2<sup>3</sup>/<sub>8</sub>" (70 mm)
  - 2<sup>3</sup>/<sub>8</sub>" (60 mm) – available
  - 3<sup>3</sup>/<sub>4</sub>" (95 mm) – available
  - 5" (127 mm) – available
- Spring Latch** • Stainless steel, 1/2" (12.7 mm) throw
- Faceplate**
  - Mortise type, square corners
  - 1<sup>1</sup>/<sub>8</sub> x 2<sup>1</sup>/<sub>4</sub>" (28.5 x 57 mm)
  - 2<sup>3</sup>/<sub>8</sub>" (60 mm) backset: 1 x 2<sup>1</sup>/<sub>4</sub>" (25.4 x 57 mm)
- Strike** • ASA Strike
- Trim**
  - Solid, pressure cast lever
  - Brass rose
  - Rose diameter: 3" (76 mm)

- Chassis**
  - Concealed mounting plate and screws
  - Removable security posts
- Preparation**
  - Cross bore: 2<sup>1</sup>/<sub>8</sub>" (54 mm)
  - Edge bore: 1" (25.4 mm)
- Cylinder**
  - Solid brass, 6-pin
  - Schlage "C" keyway, 2 keys
  - Removable, rekeyable

*Other keyways and keying options available, including CX5 high security*
- Functions**

10 Passage	60 Store*
15 Exit*	70 Classroom
17 Dummy, single	79 Institution exit*
42 Privacy	80 Storeroom
52 Entry*	82 Institution*
53 Entry	

*\*EM Lever only – see selection guide*

**Lever Styles** L–Short lever, return, M–Standard, return

**Finish** C15–Satin nickel  
C3–Polished brass

*Other finishes available by special order*

E	M	53	C15	238
SERIES	STYLE	FUNCTION	FINISH	OPTION <sup>1</sup>


(1) OPTIONS: 238 2-3/8IN (60MM) BACKSET


## SELECTION GUIDE

SERIES	FUNCTION	FINISH <sup>1</sup>	/ CASE
EL	10 Passage	C15	10
EL	17 Dummy, single	C15	20
EL	42 Privacy	C15	10
EL	53 Entry, locking thumb-turn push button ↔	C15	10
EL	70 Classroom ↔	C15	10
EL	80 Storeroom ↔	C15	10
EM	10 Passage	C15, C3	10
EM	15 Exit	C15	10
EM	17 Dummy, single	C15, C3	20
EM	42 Privacy	C15, C3	10
EM	52 Entry, locking slotted push button ↔	C15, C3	10
EM	53 Entry, locking thumb-turn push button ↔	C15, C3	10
EM	53LC Entry, less core ↔	C15, C3	10
EM	60 Store ↔	C15	10
EM	70 Classroom ↔	C15, C3	10
EM	79 Institution exit ↔	C15	10
EM	80 Storeroom ↔	C15, C3	10
EM	82 Institution ↔	C15	10

(1) OTHER FINISHES AND FUNCTIONS AVAILABLE, MINIMUM ORDER QUANTITIES AND/OR ADDITIONAL DELIVERY TIMES MAY BE REQUIRED

↔ KEYED FUNCTION; FULL KEYING SERVICES AVAILABLE



	A	B	C	D*
EL	3 (76)	3 <sup>3</sup> / <sub>8</sub> (86)	1 <sup>7</sup> / <sub>8</sub> (48)	7 <sup>7</sup> / <sub>16</sub> (11)
EM 	3 (76)	4 (102)	1 <sup>7</sup> / <sub>8</sub> (48)	7 <sup>7</sup> / <sub>16</sub> (11)

IN (MM) (\*) DIMENSION MAY VARY DUE TO DOOR THICKNESS.

## PARTS & ACCESSORIES



**9106**  
T-Strike, square corners:  
1<sup>1</sup>/<sub>8</sub> x 2<sup>3</sup>/<sub>4</sub>" (28.5 x 70 mm)



**9106NH**  
T-Strike, no hole; square corners:  
1<sup>1</sup>/<sub>8</sub> x 2<sup>3</sup>/<sub>4</sub>" (28.5 x 70 mm)

**ASA-T**  
ASA Strike, adjustable tab; square corners

**ASANH**  
ASA T-Strike, no hole; square corners



**TL020**  
Plastic spacer for latches with  
1 x 2<sup>1</sup>/<sub>4</sub>" (25.4 x 57 mm) faceplate



**TL013**  
Backset extension to 3<sup>3</sup>/<sub>4</sub>" (95 mm);  
Use with 2<sup>3</sup>/<sub>8</sub>" (60 mm) backset latch

**TL014**  
Backset extension to 5" (127 mm);  
Use with 2<sup>3</sup>/<sub>4</sub>" (70 mm) backset latch



**TL001**  
Passage latch: 2<sup>3</sup>/<sub>8</sub>" (60 mm) backset,  
1 x 2<sup>1</sup>/<sub>4</sub>" (25.4 x 57 mm) faceplate

**TL003**  
Passage latch: 2<sup>3</sup>/<sub>4</sub>" (70 mm) backset,  
1<sup>1</sup>/<sub>8</sub> x 2<sup>1</sup>/<sub>4</sub>" (28.5 x 57 mm) faceplate

**TL010**  
Privacy latch: 2<sup>3</sup>/<sub>8</sub>" (60 mm) backset,  
1 x 2<sup>1</sup>/<sub>4</sub>" (25.4 x 57 mm) faceplate

**TL002**  
Privacy latch: 2<sup>3</sup>/<sub>4</sub>" (70 mm) backset,  
1<sup>1</sup>/<sub>8</sub> x 2<sup>1</sup>/<sub>4</sub>" (28.5 x 57 mm) faceplate



**TL005**  
Deadlatch 2<sup>3</sup>/<sub>8</sub>" (60 mm) backset  
1 x 2<sup>1</sup>/<sub>4</sub>" (25.4 x 57 mm) faceplate

**TL004**  
Deadlatch: 2<sup>3</sup>/<sub>4</sub>" (70 mm) backset,  
1<sup>1</sup>/<sub>8</sub> x 2<sup>1</sup>/<sub>4</sub>" (28.5 x 57 mm) faceplate

