



- Certifications**
- Conforms to ANSI/BHMA A156.3, Grade 2
 - cULus listed, Panic Exit
 - cULus listed, up to 90 min. Fire Exit
 - 1 Year limited warranty

- Rail Assembly**
- Steel rail assembly
 - Stainless steel assembly (C32D finish)
 - Field sizable

- Handing**
- Non-handed

- Door Width**
- 30–38" (762–965 mm)
 - 36–48" (914–1219 mm)* – option
- (*) Panic Exit models only

- Door Thickness**
- 1 3/4" (45.5 mm)

- Stile Width**
- 4" (106.1 mm) minimum
- Measured from door edge

- Projection**
- 2 9/16" (65 mm) from door surface

- Latchbolt**
- Stainless steel, 3/4" (19 mm) throw
 - Deadlatch

- Strike**
- Cast iron, standard type #8000S
- Other strikes available

- Dogging**
- For Panic Exit models only
 - Hex key dogging

- Hardware**
- Machine and wood screws
 - Sex nuts & thru-bolts¹ – available

(1) Required for non-reinforced hollow metal doors, included with Fire Exit models

Electrical Options

- Trims**
- Lever, knob, pull, and handleset trims available
- Sold separately, see 8500 Trims & Accessories

- Finish**
- C28–Aluminum, painted; C3–Polished brass; C32D–Satin stainless steel
- Other finishes available by special order


8500	C32D	–	48
MODEL ¹	FINISH		OPTION

(1) SEE SELECTION GUIDE (2) OPTION: 48 –FOR DOORS 36-48X96IN (914-1219X2438MM)

SELECTION GUIDE

MODEL		DOOR WIDTH ¹	DOGGING	FINISH	/CASE
8500	Panic Exit Hardware, Rim device	30–38 (762–965)	•	C28, C3, C32D	4
8500 -48		36–48 (914–1219)	•	C28, C32D	4
8500F	Fire Exit Hardware ² Rim device	30–38 (762–965)	—	C28, C3, C32D	4

(1) RECOMMENDED DOOR WIDTH, IN (MM), FOR NON-STANDARD SIZES OR INSTALLATIONS PLEASE CONTACT. (2) FIRE EXIT HARDWARE MUST BE INSTALLED ON FIRE EXIT LABELLED DOORS.



MODEL	A	B	C	D	E ¹	F
8500 / 8500F	2 ⁹ / ₁₆ (65)	7 ¹¹ / ₁₆ (195)	2 (50.8)	20 ¹ / ₄ (514)	33 ¹ / ₄ (845)	1 ¹⁵ / ₁₆ (50)
8500 -48				30 (762)	45 ⁵ / ₁₆ (1150)	

IN (MM) (1) CAN BE CUT TO SIZE - SEE PRODUCT INSTALLATION INSTRUCTIONS

PARTS & COMPONENTS

See 8500 Trims & Accessories for additional items.



8000S
Regular ¹²/₃₂" (16.5 mm) cast iron strike for panic rim device. Included with 8500.

8000S-L
Low-profile ¹⁵/₃₂" (12 mm) cast iron strike for panic rim device. Includes ⁵/₆₄" (2 mm) shims.



8000DDS
Overlapping cast iron strike for double doors and paired panic exit devices only.

