

BHMA
CERTIFIED

G1

cUL
LISTED

3H

5

8

5
YEAR

- Certifications**
- Certified ANSI/BHMA A156.13, Series 1000, Grade 1
 - cULus listed, 3hr fire-rating
 - UL10C Positive Pressure Rated
 - Levers meet ADA (ANSI 117.1) requirements
 - 5 Year limited warranty

- Door Thickness**
- 1¾" (44.5mm)
 - 2–2¼" (51–57mm) – available

- Handing**
- Handed, field reversible

- Backset**
- 2¾" (70mm)

- Spring Latch**
- Brass, 2 piece anti-friction
 - ¾" (19mm) throw

- Deadbolt**
- Solid bolt, 2 security pins
 - 1" (25.4mm) throw

- Faceplate**
- 1¼ x 8" (32x203mm), square corners
 - Adjusts for bevelled doors up to ⅛" (3mm)

- Strike**
- ANSI strike and dust-box

- Cylinder**
- 6 pin mortise cylinder
 - Schlage "C" with 2 keys
 - Small format interchangeable core (SFIC) mortise housing available (SFIC not included)
- Other keyways and keying options available, including CX5 high security*

- Sectional Trim**
- Brass lever or knob
 - Brass rose
 - S–Round: Ø 2⅞ x ½" (61.5 x 12.7mm)
 - SQ–Square: 1⅞ x 1⅞ x ½" (48 x 48 x 12.7mm)

- Escutcheon Trim**
- Brass lever or knob
 - Brass escutcheon
 - E–Regular 2 x 8⅞ x ½" (50 x 205 x 12.7mm)
 - E2–Wide 2½ x 8⅞ x ½" (63 x 210 x 12.7mm)
 - E3–Large 2¾ x 10¾ x ½" (70 x 273 x 12.7mm)

- Chassis**
- Rose trim: concealed mounting screws
 - Thumb-turn: exposed mounting screws
 - Escutcheon: exposed mounting screws
 - Single action egress

- | | | |
|------------------|------------------------|-----------------------|
| Functions | 10 Passage | 80 Storeroom |
| | 42 Privacy | 84 Storeroom w/ |
| | 42I Privacy, indicator | deadbolt |
| | 45 Entry | 170 Dummy, surface* |
| | 50 Office | 171 Dummy, thru-bolt* |
| | 56 Dormitory | 172 Dummy, |
| | 70 Classroom | back-to-back |

(*) Sold in pairs.

- Lever Styles** A–Apollo, R–Circa, C–Cornell, D–Dartmouth, G–Glasgow, L–Linea, S–Stanford, F–The Flat, XT–Intersect

- Knob Styles** K–Kent

- Finish** 15–Satin nickel, 19–Matte black, 26D–Satin chrome
Other finishes available by special order

DM	45	L	–	SQ	F	26D
SERIES	FUNCTION	HAND ¹		TRIM	STYLE	FINISH

(1) L–LEFT R–RIGHT

SELECTION GUIDE


SERIES	TRIM	STYLE**	FUNCTION ¹	FINISH ¹	/CASE
DM	S, SQ, E, E2, E3	ALL	10 Passage	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	42 Privacy, with deadbolt	15, 19, 26D	6
DM	E	ALL	42I Privacy indicator, with deadbolt ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	45 Entry, with deadbolt ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	50 Office ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	56 Dormitory, with deadbolt ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	70 Classroom ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	80* Storeroom ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	84* Storeroom, with deadbolt ➡	15, 19, 26D	6
DM	S, SQ	ALL	170 Dummy, single (surface mount)	15, 19, 26D	6
DM	S, SQ	ALL	171 Dummy, single (thru-bolt)	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	172 Dummy, back-to-back	15, 19, 26D	6

(1) OTHER FINISHES AND FUNCTIONS AVAILABLE, MINIMUM ORDER QUANTITIES AND/OR ADDITIONAL DELIVERY TIMES MAY BE REQUIRED – PLEASE CONTACT


➡ KEYED FUNCTION; FULL KEYING SERVICES AVAILABLE – PLEASE CONTACT (*) ONE-SIDED INSTALLATION MODEL AVAILABLE (**) XT / INTERSECT NOT AVAILABLE WITH ESCUTCHEON

LEVERS & KNOBS


A–Apollo




C–Cornell




D–Dartmouth




F–The Flat




G–Glasgow




L–Linea




R–Circa




S–Stanford



XT–Intersect



K–Kent



STYLE	A	B	C ¹
A–Apollo*	3 ¹ / ₁₆ (78)	4 ⁵ / ₈ (116)	2 ¹ / ₁₆ (53)
C–Cornell	2 ⁷ / ₈ (73)	5 ⁵ / ₁₆ (134)	⁵ / ₈ (16)
D–Dartmouth	2 ⁷ / ₁₆ (61.5)	5 ⁷ / ₈ (149)	1 ¹ / ₁₆ (17)
F–The Flat	2 ⁷ / ₈ (73)	5 ¹ / ₂ (139.7)	2 ³ / ₁₆ (55.5)
G–Glasgow	2 ⁷ / ₈ (73)	5 ¹ / ₁₆ (128)	2 ¹ / ₁₆ (52)

IN (MM) (1) ALL ROSES AND ESCUTCHEONS ARE 12.7 (1/2) THICK


STYLE	A	B	C ¹
L–Linea	2 ¹³ / ₁₆ (71.4)	5 (127)	1 ¹⁵ / ₁₆ (48.4)
R–Circa	2 ⁹ / ₁₆ (65.5)	5 ¹ / ₂ (139.7)	1 ⁷ / ₈ (47)
S–Stanford	2 ⁹ / ₁₆ (65.5)	5 ¹ / ₁₆ (128)	⁹ / ₁₆ (14)
XT–Intersect*,**	2 ¹⁹ / ₆₄ (56)	4 ¹⁵ / ₁₆ (125)	¹ / ₂ (12.7)
K–Kent	2 ⁷ / ₁₆ (61.5)	ø 2 (50.8)	—

(*) HANDED LEVER, NOT FIELD REVERSIBLE,

(**) SECTIONAL ONLY, NOT AVAILABLE WITH ESCUTCHEON




LOCK TRIMS



TRIM	E ¹	E2	E3 ²	S	SQ
Description	Regular escutcheon	Wide escutcheon	Large escutcheon	Round rose	Square rose
Width (W)	2 (50)	2 1/2 (64)	2 3/4 (70)	ø 2 3/8 (60)	1 7/8 (48)
Height (H)	8 1/16 (205)	8 1/4 (210)	10 3/4 (273)	—	1 7/8 (48)
Depth (D)	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)
Material	Brass	Brass	Brass	Brass	Brass

IN (MM) (1) AVAILABLE WITH PRIVACY INDICATOR—421 (2) OPTIONAL ENGRAVING AVAILABLE—PLEASE CONTACT

DIMENSIONS



MUST BE INSTALLED ON A DOOR WITH A SOLID LOCK STILE WIDTH OF AT LEAST 5" (127 MM) OR WITH APPROPRIATE REINFORCEMENT.

⚠ WHEN USED WITH ELECTRIC STRIKE PLEASE REQUEST ADDITIONAL INFORMATION.

PARTS & ACCESSORIES



DM45X-PS

Replacement strike for 1 3/4 (45) thick door.
(Functions 42, 45, 56, 84)



DM80X-PS

Replacement strike for 1 3/4 (45) thick door.
(Functions 10, 50, 70, 80)



DM45X-PE

Mortise lock emergency privacy key; round.
Includes plate and screws.



DM45X-PES

Mortise lock emergency privacy key; square.
Includes plate and screws.



DM45X-PT

Mortise lock thumbturn; round. Mounting screws included.
Finish: 15, 19, 26D



DM45X-PTS

Mortise lock thumbturn; square. Mounting screws included.
Finish: 15, 19, 26D



DM00X-PPRVI

Occupancy indicator. Includes round interior/ exterior trims for use with privacy (42) function. For 1 3/4" (44.5) thick wood door. Mounting hardware included. Finish: 15, 26D



DM00X-PPRVIQ

Occupancy indicator. Includes square interior/ exterior trims for use with privacy (42) function. For 1 3/4" (44.5) thick wood door. Mounting hardware included. Finish: 15, 26D



DM00X-PPRVI-ECYL

Keyed occupancy indicator. Includes round interior/ exterior trims for use with keyed functions 45, 56, or 84. For 1 3/4" (44.5) thick wood door. Mounting hardware and DM00X-ECYL cylinder with 2 keys included. Finish: 15, 26D



DM00X-PPRVIQ-ECYL

Keyed occupancy indicator. Includes square interior/ exterior trims for use with keyed functions 45, 46, or 84. For 1 3/4" (44.5) thick wood door. Mounting hardware and DM00X-ECYL cylinder with 2 keys included. Finish: 15, 26D



DM45X-PR

Mortise cylinder collar with spring; round.
Ø 1 11/16 x 3 7/8 (Ø 43 x 9)
Finish: 15, 19, 26D



DM45X-PRS

Mortise cylinder collar with spring; square.
1 7/8 x 1 7/8 x 3 7/8 (48 x 48 x 9)
Finish: 15, 19, 26D



DM00X-PSCYL

- 1 1/8 (28.6) 5-pin (drilled 6) brass mortise cylinder; Schlage "C" with 2 keys.
 - For sectional installations on 1 3/4 (45) thick doors.
 - Includes DM00X-PCAM.
- Finish: 15, 19, 26D

DM00X-PECYL

- 1 1/4 (31.8) 5-pin (drilled 6) brass mortise cylinder; Schlage "C" with 2 keys.
 - For escutcheon installations on 1 3/4 (45) thick doors.
 - Includes DM00X-PCAM.
- Finish: 15, 19, 26D



DM00X-PCAM

Replacement mortise cylinder cam, with screws

NOTE: OTHER CYLINDERS MAY REQUIRE A DIFFERENT CAM. PLEASE CONTACT IF USING A DIFFERENT CYLINDER. OTHER CAMS SOLD SEPARATELY.



DM00X-PKDT225

- Installation kit for 2-2 1/4 (51-57) thick doors.
- Includes extended thumb-turn, spindle, springs, strike and mounting hardware for rose or escutcheon trim.
 - Mortise cylinder NOT INCLUDED.
- Please contact for details.

