



- Type** • Cylindrical lock
- Certifications**
 - Conforms to ANSI/BHMA A156.2, Series 4000, Grade 2
 - cULus listed, 3hr fire-rating
 - UL 10C Positive Pressure Rating
 - Meets ADA requirements
 - 1 Year limited warranty
- Door Thickness** • 1³/₈ – 1³/₄" (35–44.5 mm)
- Handing** • Non handed
- Backset**
 - 2³/₈" (70 mm)
 - 2³/₈" (60 mm) – available
 - 3³/₄" (95 mm) – available
 - 5" (127 mm) – available
- Spring Latch** • Stainless steel, 1/2" (12.7 mm) throw
- Faceplate**
 - Mortise type, square corners
 - 1¹/₈ x 2¹/₄" (28.5 x 57 mm)
 - 2³/₈" (60 mm) backset: 1 x 2¹/₄" (25.4 x 57 mm)
- Strike** • ASA Strike
- Trim**
 - Solid, pressure cast lever
 - Brass rose
 - Rose diameter: 3" (76 mm)

- Chassis**
 - Concealed mounting plate and screws
 - Removable security posts
- Preparation**
 - Cross bore: 2¹/₈" (54 mm)
 - Edge bore: 1" (25.4 mm)
- Cylinder**
 - Solid brass, 6-pin
 - Schlage "C" keyway, 2 keys
 - Removable, rekeyable

Other keyways and keying options available, including CX5 high security
- Functions**

10 Passage	53 Entry
17 Dummy, single	70 Classroom
42 Privacy	80 Storeroom
- Lever Styles** L–Short lever, return
- Finish** C15–Satin nickel
Other finishes available by special order

E	L	53	C15	238
SERIES	STYLE	FUNCTION	FINISH	OPTION ¹


(1) OPTIONS: 238 2-3/8IN (60MM) BACKSET

SELECTION GUIDE

SERIES	FUNCTION ¹	FINISH ¹	/ CASE
EL	10 Passage	C15	10
EL	17 Dummy, single	C15	20
EL	42 Privacy	C15	10
EL	53 Entry, locking thumb-turn push button	C15	10
EL	70 Classroom	C15	10
EL	80 Storeroom	C15	10

(1) OTHER FINISHES AND FUNCTIONS AVAILABLE, MINIMUM ORDER QUANTITIES AND/OR ADDITIONAL DELIVERY TIMES MAY BE REQUIRED

• KEYED FUNCTION; FULL KEYING SERVICES AVAILABLE



	A	B	C	D*
EL	3 (76)	3 ³ / ₈ (86)	1 ⁷ / ₈ (48)	7 ¹ / ₁₆ (11)

IN (MM) (*) DIMENSION MAY VARY DUE TO DOOR THICKNESS.

PARTS & ACCESSORIES



9106
T-Strike, square corners:
1¹/₈x2³/₄" (28.5x70 mm)



9106NH
T-Strike, no hole; square corners:
1¹/₈x2³/₄" (28.5x70 mm)

ASA-T
ASA Strike, adjustable tab; square corners

ASANH
ASA T-Strike, no hole; square corners



TL020
Plastic spacer for latches with 1 x 2¹/₄"
(25.4x57 mm) faceplate to fit preparations
for 1¹/₈x2¹/₄" (28.5x57 mm) faceplates



TL013
Backset extension to 3³/₄" (95 mm);
Use with 2³/₈" (60 mm) backset latch

TL014
Backset extension to 5" (127 mm);
Use with 2³/₄" (70 mm) backset latch



TL001
Passage latch: 2³/₈" (60 mm) backset,
1x2¹/₄" (25.4x57 mm) faceplate

TL003
Passage latch: 2³/₄" (70 mm) backset,
1¹/₈x2¹/₄" (28.5x57 mm) faceplate

TL010
Privacy latch: 2³/₈" (60 mm) backset,
1x2¹/₄" (25.4x57 mm) faceplate

TL002
Privacy latch: 2³/₄" (70 mm) backset,
1¹/₈x2¹/₄" (28.5x57 mm) faceplate



TL005
Deadlatch 2³/₈" (60 mm) backset
1x2¹/₄" (25.4x57 mm) faceplate

TL004
Deadlatch: 2³/₄" (70 mm) backset,
1¹/₈x2¹/₄" (28.5x57 mm) faceplate

TL006
Deadlatch: 5" (127 mm) backset,
1¹/₈x2¹/₄" (28.5x57 mm) faceplate

