



- Type** • Cylindrical lock
- Certifications** • Conforms to ANSI/BHMA A156.2, Series 4000, Grade 2
• cULus listed, 3hr fire-rating
• UL 10C Positive Pressure Rating
• Meets ADA requirements
• 10 Year limited warranty
- Door Thickness** • 1 $\frac{3}{8}$ –2" (35–51 mm)
- Handing** • Non handed
- Backset** • 2 $\frac{3}{4}$ " (70 mm)
• 2 $\frac{3}{8}$ " (60 mm) – available
• 3 $\frac{3}{4}$ " (95 mm) – available
• 5" (127 mm) – available
- Spring Latch** • Stainless steel, 1 $\frac{1}{2}$ " (12.7 mm) throw
• Deadlatch, 3 $\frac{1}{4}$ " (19 mm) throw – available
- Faceplate** • Mortise type, square corners
• 1 $\frac{1}{8}$ x2 $\frac{1}{4}$ " (28.5x57 mm)
- Strike** • ASA Strike
- Trim** • Solid, pressure cast lever
• Brass rose
• Rose diameter: 3 $\frac{5}{16}$ " (84.5 mm)

- Chassis** • Concealed mounting plate and screws
• Removable security posts
• Lever clutch release – option

- Preparation** • Cross bore: 2 $\frac{1}{8}$ " (54 mm)
• Edge bore: 1" (25.4 mm)

- Cylinder** • Solid brass, 6-pin
• Schlage "C" keyway, 2 keys
• Removable, rekeyable

Other keyways and keying options available, including CX5 high security

- | | | |
|------------------|------------------|--------------|
| Functions | 00 Dummy, single | 53 Entry |
| | 10 Passage | 70 Classroom |
| | 40 Privacy | 80 Storeroom |

- Lever Styles** H–Standard return

- Finish** 26D–Satin chrome

Other finishes available by special order

T2	H	53	–	26D	–	C
SERIES	STYLE	FUNCTION		FINISH		OPTION*


(*) C: CLUTCH; OTHER OPTIONS AVAILABLE, PLEASE CONTACT FOR DETAILS

SELECTION GUIDE

SERIES	STYLE	FUNCTION ¹	FINISH ¹	/ CASE
T2	H	00 Dummy, single	26D	12
T2	H	10 Passage	26D	6
T2	H	40 Privacy, push button thumb-turn	26D	6
T2	H	53 Entry 	26D	6
T2	H	70 Classroom 	26D	6
T2	H	80 Storeroom 	26D	6

(1) OTHER FINISHES AND FUNCTIONS AVAILABLE, MINIMUM ORDER QUANTITIES AND/OR ADDITIONAL DELIVERY TIMES MAY BE REQUIRED

 KEYED FUNCTION; FULL KEYING SERVICES AVAILABLE



	A	B	C	D*
T2H 	3 ⁵ / ₁₆ (84.5)	4 ¹ / ₂ (114)	2 ⁵ / ₁₆ (58.7)	3 ³ / ₈ (9.5)
IN (MM)	(*) DIMENSION MAY VARY DUE TO DOOR THICKNESS.			

PARTS & ACCESSORIES



9106

T-Strike, square corners:
1 ¹/₈ x 2 ³/₄ " (28.5 x 70 mm)

9106NH

T-Strike, no hole; square corners:
1 ¹/₈ x 2 ³/₄ " (28.5 x 70 mm)



ASA-T

ASA strike with adjustable tab

ASANH

ASA strike, no hole



TL020

Plastic spacer for latches with 1 x 2 ¹/₄ " (25.4 x 57 mm) faceplate to fit preparations for 1 ¹/₈ x 2 ¹/₄ " (28.5 x 57 mm) faceplates



TL013

Backset extension to 3 ³/₄ " (95 mm);
Use with 2 ³/₈ " (60 mm) backset latch

TL014

Backset extension to 5 " (127 mm);
Use with 2 ³/₄ " (70 mm) backset latch



TL001

Passage latch: 2 ³/₈ " (60 mm) backset,
1 x 2 ¹/₄ " (25.4 x 57 mm) faceplate

TL003

Passage latch: 2 ³/₄ " (70 mm) backset,
1 ¹/₈ x 2 ¹/₄ " (28.5 x 57 mm) faceplate

TL010

Privacy latch: 2 ³/₈ " (60 mm) backset,
1 x 2 ¹/₄ " (25.4 x 57 mm) faceplate

TL002

Privacy latch: 2 ³/₄ " (70 mm) backset,
1 ¹/₈ x 2 ¹/₄ " (28.5 x 57 mm) faceplate



TL005

Deadlatch: 2 ³/₈ " (60 mm) backset,
1 x 2 ¹/₄ " (25.4 x 57 mm) faceplate

TL004

Deadlatch: 2 ³/₄ " (70 mm) backset,
1 ¹/₈ x 2 ¹/₄ " (28.5 x 57 mm) faceplate

TL006

Deadlatch: 5 " (127 mm) backset,
1 ¹/₈ x 2 ¹/₄ " (28.5 x 57 mm) faceplate



GX1DL234-34

Deadlatch: 2 ³/₄ " (70 mm) backset, ³/₄ " (19 mm) throw, 1 ¹/₈ x 2 ¹/₄ " (28.5 x 57 mm) faceplate
For use in double door or electric strike applications

